

# SC-TOP - Refractory sets

Overview and specifications



- The SC-kilns are delivered Ready-To-Use, complete with controller, CEE-plug and manuals. -Get started on day one!
- Kiln pack including refractory set, Cordierite -Mullite batts and tubes in various sizes for temperatures up to 1300 °C.
- Including Batt wash, a protective coating for kiln batts, to protect the batts from dripping glazes during firing.

### **CONTACT INFORMATION**

### **CEBEX Keramikexperterna AB**

#### Malmoe

Erlandsrovägen 3 S-218 45 VINTRIE Tel +46 40 - 671 77 60 Fax +46 40 - 671 77 61

#### Stockholm

Hammarby Fabriksväg 43 S-120 33 STOCKHOLM Tel +46 8 - 658 50 04 Fax +46 8 - 669 60 98

### Gothenburg

Argongatan 8 S-431 53 MÖLNDAL Tel +46 31 - 87 51 30 Fax +46 31 - 87 97 61

Web www.cebex.se Mail Info@cebex.se

## General



In our product range on refractories you can find a wide variety of shapes and sizes i.e. Pressed Batts  $1000 \times 1000 \text{ mm}$ , Extruded Batts up to  $1800 \times 840 \text{ mm}$  and Circular Discs up to 1092 mm dia.

We offer a range of designs to suit your individual needs and accessories such as props, caps, beams and fittings combine to allow a complete support system to be assembled.

The refractories for the SC-TOP series has carefully been selected to make sure that we meet the demands as for quality and usability. Each kiln model is delivered with a refractory set including batts, tubes and batt wash. The refractory sets are adapted to fitt the size of the kiln (the picture above is only showing a typical set), see next page.



## Refractory set SC-Kilns

SC TOP 020 - SC200

The refractory sets for the SC-kilns series are produced in a good general-purpose material (cordierite-mullite) with reasonable resistance to thermal shock and good cold strength. It is not recommended for use under heavy loads at high temperatures above 1300 °C or in very fast-firing kilns.

Normally the batts will bend at the high temperatures and should be repeatedly flipped to remain straight. Note! Do not use bended batts in your production.

574002000

It is recomended to apply the Batt wash, a protective coating for kiln batts (also included in the sets), to protect the batts from dripping glazes during firing. Mix the powder with water to a creamy consistency and apply with a brush.

## **SC TOP-020**

574sc020s				574sc020s
Item	Description	Vol	Price	Total
5722813	S-batt 280 x 13 mm	2	205,00	410,00
57350	S-tube 50 mm	3	14,70	44,10
573100	S-tube 100 mm	3	22,10	66,30
	To	otal sum Sl	ΞK, EXW	520,00

### **SC TOP-065**

SC TOP-005 574sc				574sc065s
Item	Description	Vol	Price	Total
5723510	S-batt 350 x 10 mm	3	195,00	585,00
57325	S-tube 25 mm	3	12,00	36,00
57350	S-tube 50 mm	3	14,70	44,10
57375	S-tube 75 mm	3	18,60	55,80
573100	S-tube 100 mm	3	22,10	66,30
573	Batt Wash (Pulver)	1	70,80	70,80
Total sum SEK, EXW			EK, EXW	858,00

### **SC TOP-100**

				5/4sc100s
Item	Description	Vol	Price	Total
5723510	S-batt 350 x 10 mm	n 3	375,00	1 125,00
57325	S-tube 25 mm	3	12,00	36,00
57350	S-tube 50 mm	3	14,70	44,10
57375	S-tube 75 mm	3	18,60	55,80
573100	S-tube 100 mm	3	22,10	66,30
573	Batt Wash (Pulver)	1	70,80	70,80
Total sum SEK, EXW		1 398,00		

### **SC TOP-150**

				574sc150s
Item	Description	Vol	Price	Total
5723510	S-batt 350 x 10 mn	n 3	425,00	1 275,00
57325	S-tube 25 mm	3	12,00	36,00
57350	S-tube 50 mm	3	14,70	44,10
57375	S-tube 75 mm	3	18,60	55,80
573100	S-tube 100 mm	3	22,10	66,30
573150	S-tube 150 mm	3	40,00	120,00
573	Batt Wash (Pulver)	1	70,80	70,80
Total sum SEK, EXW		1 668,00		

### **SC TOP-200**

				574802008
Item	Description	Vol	Price	Total
5723510	S-batt 350 x 10 mm	3	525,00	1 575,00
57325	S-tube 25 mm	3	12,00	36,00
57350	S-tube 50 mm	3	14,70	44,10
57375	S-tube 75 mm	3	18,60	55,80
573100	S-tube 100 mm	3	22,10	66,30
573150	S-tube 150 mm	3	40,00	120,00
573	Batt Wash (Pulver)	1	70,80	70,80
Total sum SEK, EXW		1 968,00		



\* Mix the Batt Wash with water until a milky consistency and apply crosswise with a soft brush i.e. item no. 344121 in the picture.

